



PERMANENT DOCUMENT

ENEC 303
Annex AC

Annex AC
to Routine Test Requirements for manufacturers
(as per Article 9 of the Agreement)

Lamp control gear covered by
EN 61347-2-10, -2-11, -2-12 and -2-13
EN 62384 to be used with part 2-13 (performance)

~~Text strikethrough~~ deleted
Text in red colour added

Text in blue color – modifications on comments of the member during voting

Approved by:	Electronic vote closed on 14 August 2019	Nr of pages: 3
Date of issue:	August 2019	
Supersedes:	PD ENEC 303 Annex AC - September 2012	Page 1 of 3

Annex AC to PD ENEC 303

Lamp control gear covered by EN 61347-2-10, -2-11, -2-12 and -2-13 EN 62384 to be used with part 2-13 (performance)

1 ROUTINE TESTS (100%)

1.1 Inspection

Visual inspection shall take place to ensure that:

- a) all specified labels are securely in place;
- b) manufacturers' instructions are placed with the control gear, where necessary;
- c) visual inspection of control gear for completeness and mechanical check against a checklist for the product.

1.2 Operating check

The control gear shall be connected with proper **lamp light source** for the correct operating.

Otherwise a circuit giving sufficient assurance of correct operating can be used, as alternative.

1.3 Dielectric strength test

Voltage test applied for a period of 1 second as indicated in the following table:

Application point of voltage test	Self-equivalent converters >200 and ≤450 V	Isolating converters control gears (self-converters) (SELV control gears) >200 and ≤450 V	Other converters control gears >42 and ≤1000 V >50 and ≤1000 V
Between live parts (input and output live parts) and the body	1500 V	1875 V 1500 V a.c. or 1500√2 V d.c.	2 U + 1000 V a.c. or 2 U + 1000 √2 V d.c.
Between input live Parts and output live parts	3000 V	3750 V 3000 V a.c. or 3000√2 V d.c.	

In case of built-in or integral control gear testing shall be applied according to the final installation.

1.4 Protective earth continuity (only for class I)

In a circuit with an input between 6 and 12 V AC a current of 25 A (or 10 A as alternative) has to pass between the earthing terminal or earthing contact and each accessible metallic part that may become live in case of insulation defect.

Under any circumstances, the contact resistance must not exceed 0,5 Ω .

PRODUCT VERIFICATION TESTS (PVT)

- 2.1 Endurance test (at least once a year if included in the relevant performance standard).
This test shall be carried out on the most critical type of each range of control gear.
 - 2.2 Terminals, screws, current-carrying parts and connections (at least once a year).
 - 2.3 Protection against accidental contact with live parts and creepage distances and clearances measurement (at least once a year).
 - 2.4 Abnormal conditions (at least once a year).
-